



NOTE :- REMOVE ALL BURRS & SHARP EDGES, CORNER ETC.

DRD T 303/604 D.D. - 609		LEG REAR		4	STEEL RHS	IS: 4923 YST. 310	
THICKNESS OF RHS CHANGED FROM 6 ± 0.5 TO 6.6 ± 10%.		वर्णन DESCRIPTION		संख्या/ रेलइंजन NO./ LOCO	पदार्थ MATL	विशिष्टि SPECN	प्रति भाग कि. ग्रा. WT. EACH IN K.G.
DY.CEE D/CONV		अभिकल्पित DGN		आरेखण संदर्भ REF. ASS'LY DRG. NO. - ABB DRG. NO. - 1B026-00909,910		अभिकल्प एवं विकास केन्द्र D & D CENTRE चित्तारंजन रेलइंजन कारखाना	
DY.CEE D/CONV		जोचा CHD		ITEM I OF DRG. NO. 1209-02.327.063 A & B		CHITTARANJAN LOCOMOTIVE WORKS	
DY.CEE D/CONV		अर्धसिक SUPDT.		संस्वरे क. CAD NO.		प्रयोग में USED FOR LOCOS	
DY.CEE D/CONV		समीक्षित व.अ (स/वि) REVIEWED SE (M/E)		WAG-9 (COLO)		1ST. ANGLE PROJECTION	
DY.CEE D/CONV		अनुमोदित (अ.वि) APPROVED व.म. वि.अ DYCEE		LEG REAR		आरेखण संख्या DRAWING NO.	
DY.CEE D/CONV		दिनांक DATE		30-01-02		1209-02-427.064	
DY.CEE D/CONV		रैखिक अनुपात SCALE		N.T.S.			
DY.CEE D/CONV		संदर्भ/REF.					