

**SPECIFICATION FOR FIRE EXTINGUISHING SYSTEM TO BE
USED ON WAG-9 (Co-Co)/ WAP-5(Bo-Bo) 3-PHASE A.C.
ELECTRIC LOCOMOTIVE FOR INDIAN RAILWAYS.**

SPECIFICATION NO. CLW/MS/3/108 ALT.8
ISSUE DATE: 08.02.2000.

ISSUED BY:

DY. CHIEF ELECTRICAL ENGINEER/D/CONV.

CHITTARANJAN LOCOMOTIVE WORKS

P.O. CHITTARANJAN – 713331

DIST. BARDHAMAN (WEST), WEST BENGAL (INDIA)

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III

ALTERATION RECORD SHEET

ALT. No.	DATE	DESCRIPTION	REASON	SIGNATURE
1	19.03.2002	PARA 7.7 ADDED	AS DECIDED BY COMPETENT AUTHORITY VIDE LETT. NO.C – D&D/ TOT/111 DT. 18.02.2002	S/d- 19.03.2002
2	30.05.2002	CLAUSE 10 ADDED	TO EASE ASSY. AND FITMENT VIDE L/No. C – D&D/ TOT/165 DT. 18.04.2001	S/d- 30.05.2002
3	21.11.2002	SL. No. 13 MODIFIED DRG. NO. 1209-00-340-109 TO BE FOLLOWED BY ALT.2	TO AVOID CONFUSION	S/d- 21.11.2002
4	14.01.2004	ALT.3 AGAINST DRG. NO. 1209-00-340-109 AND ALT. NO.4 AGAINST SPEC. ARE ADDED.	TO UPDATE SPEC.	S/d- 14.01.2004
5	12.02.2008	NEW DRG. NO. FOR WAP-5 ADDED IN THIS SPEC. AND PARA 10 (ii) ADDED.	NEW DRG. NO. FOR WAP-5 INCORPORATED	S/d- 12.02.2008
6	09.02.2011	NEW DRG. 1209-00-240-109 ALT.5 GENERATED INSTEAD DRG. NO. 1209-00-340-109 ALT.4 CHART OF PIPE SIZE AND QTY/LOCO DELETED. CHART INTRODUCE AT DRG.	ADDITION OF NEW PIPE FITTING INCREASING QTY/LOCO OF FITTINGS FOR PROPER FITMENT ACCORDING LAYOUT OF PIPE LINE FOR EXTINGUISHING SYSTEM AND REQUISITION OF CLW ASSY. SHOP-16.	S/d- 11.02.2011
7	25.07.2018	ALTERED LENGTHS OF ST. ST. TUBES FOR WAP-5 LOCO ADDED AT PARA 10 (i) & DELETED PARA 10 (ii). REVISED PARA 4.7.6 & 7.	CONVENIENCE OF WORK, PROPER FITMENT & EASY ACCESS AS TO VARIOUS JOINTS AS REQUIRED BY ASSY. SHOP.	S/d- 27.07.2018
8		(i) Alt No. is added to Drg. No. 1210-02.340-076 at clause 2.1 & 4.20 (ii) Clause No. 4.7.1, 4.9, 4.10, 4.14, 4.18, 5.1, 6.1, 6.3, 7.1, 7.4, 7.5, 7.6 & 10 are modified.	Specification has been altered in accordance with latest IS and drawing.	

Specification have been digitized and all alterations have been incorporated

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III

TABLE OF CONTENTS

SL. No.	Description of contents	Page No.
1	Scope	4
2	Scope of supply	4
3	General	4
4	Technical Requirements	4-6
5	Performance requirement	6
6	Manufacture	6
7	Inspection and Testing	6-7
8	Marking & identification	7
9	Packing & Delivery	7
10	Schedule	8

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III

TECHNICAL SPECIFICATION OF FIRE EXTINGUISHING SYSTEM TO BE USED ON WAG-9 (Co-Co) / WAP-5(Bo-Bo) 3-PHASE A.C. ELECTRIC LOCOMOTIVE FOR INDIAN RAILWAYS.

1. SCOPE:

This specification covers the minimum requirement of design, manufacturing, supply and installation conditions of Fire extinguishing system to be used on WAG-9 (Co-Co) / WAP-5(Bo-Bo) 3-phase A.C. electric locomotive for Indian Railways.

2. SCOPE OF SUPPLY :

2.1 One set of whole system of Fire extinguishing CO₂ gas of 22.5kg capacity, to be supplied per loco as per attached Drg. No. – 1209-00.240-109 ALT-7 or latest meant for WAG-9 class of loco. Qty per set will be equal to the quantity per loco as indicated against each item & Drg. No. -1210-02.340-076 **ALT.1 or latest** for WAP-5 loco.

2.2 Maintenance procedure and inspection schedule required to maintain the extinguishing system in good working order, to be supplied along with fire extinguishing system.

3. GENERAL

3.1 The Fire extinguishing system with pipe, intended to operate manually, is installed in the loco with its entire length of side wall (both side) in the machine compartment, having 22.5kgs capacity CO₂ gas cylinders installed outside of the machine compartment i.e. in cup-board to operate from driver's cabin more effectively instead of rushing inside the compartment. to extinguish the fire involving carbonaceous solids, flammable and combustible liquids, oil, cables, rubber, energized electrical equipments etc. This specn. based on RDSO's Letter no. EL/3.1.35/2 dt. 15.10.98.

4. TECHNICAL REQUIREMNT:

4.1 The carbon di-oxide gas of fire extinguishing system shall be capable to extinguish the fires involving carbonaceous solids, wood, cloth, cables, paper, rubber, plastics, flammable and combustible liquids, oil, energized equipments etc.

4.2 Shall be suitable for an installation in dynamic vehicle under continuous vibration and shocks and impact load up to 5 cm/s/s.

4.3 In order to gain access to awkward location, the gas discharge jet shall be designed in such a manner to extinguish the fire effectively.

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III

- 4.4 The extinguisher shall be provided with a safety device in the actuating mechanism to prevent accidental operation.
- 4.5 The length of seamless steel pipe N. Bore 1/4" with socket joint to be such to cover entire length of loco sidewall LHS and RHS with discharge jet at four places, as indicated in the drawing, which extinguish the fire effectively.
- 4.6 The extinguish act shall be electrically non-conductive and designed to operate in the normal vertical position.
- 4.7 Each fire extinguishing cylinder shall be provided with two nos. of pressure gauges with graduated marks and indicator.
- 4.7.1 Two nos. of carbon di-oxide gas cylinder each capacity 22.5 Kg. conforming to ~~IS:2872~~ IS: 16018 with charged weight 70 Kg.
- 4.7.2 Four nos. of diffusers with nozzles.
- 4.7.3 Seamless st. st. pipe nom. Bore 6.4mm & O/D 10mm to ASTM-A 269 Gr.304.
- 4.7.4 Wheel cock - 2 Nos.
- 4.7.5 Isolating cock - 2 Nos.
- 4.7.6 Discharge flexible hose - 2 nos.1.0 meters each lg. with horn.
- 4.7.7 Pipe. clamp 30-nos.with St. St. HEX. Hd. screw M6x12 of Gr. ISO 4017 A4-70.
- 4.8 Pressure developed in a correctly charged extinguisher during operation at a temp. of 65°C shall be capable to discharge the gas continuously for the specified period.
- 4.9 The body of the cylinder shall be of seamless steel conforming to ~~IS:2872~~ IS: 7285. The external surface of cylinder shall be treated to resist atmospheric corrosion.
- 4.10 Discharge time shall be ~~20 minutes~~ 20 seconds minimum and ~~60 minutes~~ 60 seconds maximum.
- 4.11 Proper sealing arrangement shall be provided on wheel cock in order to avoid inadvertent operation.
- 4.12 Fire extinguishing system is intended to be operated manually by the drivers.
- 4.13 The pipe lines shall be interconnected at one end to other take care of the Situation when one carbon di-oxide fire extinguisher becomes defective/in-operational due to some problem.
- 4.14 Liquified carbon di-oxide gas used for extinguisher shall conform to ~~IS:307~~ IS:15222 filled with filling 0.667 with tolerance ± 0.017 . The quantity shall be determined by weighing
- 4.15 There shall be no leakage of carbon di-oxide from valve or fittings during or before use of extinguisher.
- 4.16 Operational method and inspection schedule shall be written on the body in Hindi & English.

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III

4.17 Period for refilling/checking should be clearly mentioned on the body.

4.18 The material used for body, internal discharge diffuser, discharge hose, wheel cock, isolating cock and other conditions shall conform to ~~IS:2878-86~~ IS: 16018.

4.19 It should also designed to withstand without rupture of a pressure of not less than 4 times the equilibrium pressure when operated at 65°C temperature with outlet blocked.

4.20 Installation shall be as per drg. No. 1209-00.240-109 Alt.7 or latest for WAG-9 loco and Supplier shall confirm the system satisfactorily after installing in the loco (only on prototype) & installation shall be as per drg. No. 1210-02.340-076 ALT.1 or latest for WAP-5 loco.

5. PERFORMANCE REQUIREMENT :

5.1 The design and construction of fire extinguishing system shall be such that when operated at 27°C, it shall expel carbon di-oxide gas in uniform of continuous discharge for minimum ~~20 minutes~~ 20 seconds from the time of operating the valve.

5.2 Shall also conform the correct discharge rate and speed of jetting.

6. MANUFACTURE:

6.1 Body of extinguisher shall be a seamless cylinder manufactured to ~~IS :2872~~ IS:7285. The external surface of the cylinder shall be treated or coated to resist atmospheric corrosion.

6.2 The actuating mechanism shall be made of non-ferrous metal or stainless steel of high strength and be so designed that necessary operation for extinguishing shall be simple and obvious.

6.3 Material used for manufacturing isolating cock, diffuser pipe, wheel cock etc. which are the constituents of supply, shall be conformed the condition laid down in ~~IS :2878-86~~ IS:16018.

6.4 Each extinguisher shall be supplied with all the items shown in drawing with spanner.

7. INSPECTION & TESTING:

7.1 ~~Each extinguisher body shall be passed the hydraulic stretch and pressure test according to IS : 2872, which shall be not less than 1.5 times in equilibrium pressure 2.5 Mpa at 70°C.~~

7.1 Each extinguisher body shall be passed the hydraulic stretch and pressure test according to IS:7285, which shall not be less than $250Kg/cm^2$.

7.2 Sealing device of actuating mechanism shall be checked.

7.3 Discharge test to be conducted by supplier to check the discharge time of liquefied gas, distance and residue during demonstration.

7.4 Authorized representative of CLW ~~respective inspection agency~~ will inspect the material and mechanism at firm's premises. All the tests shall be conducted and borne by supplier. Being a safety

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III

item defective material if any shall not be accepted.

7.5 ~~Hose assly. with its coupling shall be tested to the min. working pressure of 315 Kg/Sq.cm without failure.~~

7.5 The Hose assembly with its coupling shall be tested to the minimum burst pressure of 1.5 times the pressure developed in the extinguisher at 55°C, the test being carried out at $27 \pm 2^\circ\text{C}$ and 1.25 times the pressure developed in the extinguisher at 55°C, the test being carried out at $55 \pm 5^\circ\text{C}$ as per clause 8.11.3(b) of IS:16018.

7.6 Extinguisher showing loss of weight of gas **exceeding (-) 5%** shall be rejected.

7.7 (i) Prior to prototype inspection CLW'S representative will be deputed to seal the sample piece of the material specified for test in the government approved/ RDSO approved test lab. The lab test report should be produced at the time of prototype inspection.

(ii) Standard Fasteners of M/s. TVS, M/s. LPS and M/s UNBREAKO & M/s KUNDAN only shall be used in the assembly.

8. MARKING AND IDENTIFICATION :

Every extinguisher shall be marked with the following:

- a) Instruction for operation and name of gas.
- b) The capacity in Kilogram.
- c) Name and Address of Manufacturer with Trade Mark.
- d) The working pressure in Kg/cm² or mega Pascal.
- e) The overall weight of the Extinguisher when full.
- f) The Year and Month of Manufacture with IS Specification.
- g) Period for refilling/checking.

9. PACKING & DELIVERY:

9.1 The fire extinguisher system shall be supplied complete in all respect as laid down in specification, properly protect from damage or deterioration and ready for successful operation.

9.2 For other details, terms & conditions refer bid document.

9.3 Supplier can contact C-D&D/CLW for any improvement prior to manufacture.

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III

10. Tubes, threaded at both ends should be supplied as per the following schedule:-

i. Ref. Drg. No- 1210-02.340-076 Alt.1 for WAP-5 loco.

SL. No.	LENGTH IN mm	QUANTITY	TOTAL LENGTH (mm)
1.	2525	1	2525
2.	2600	1	2600
3.	3325	1	3325
4.	2470	1	2470
5.	2610	1	2610
6.	1840	1	1840
7.	1630	1	1630
8.	3400	1	3400
9.	150	2	300
10.	955	1	955
11.	1040	1	1040
12.	90	2	180
13.	450 (Bend at 20° at one end)	4	1800

PREPARED BY	CHECKED BY	APPROVED BY
SSE/DRG&DGN (M)	SSE/DRG	DY. CEE/D-III