



NOTE:

- SEAT IS DESIGNED AS PER STANDARD UIC- 651/612.
- PU CUSHIONING COVERED WITH FIRE BARRIER, FIRE BARRIER COVER AS PER EN45545 HL3
- OUTER LAYER MATERIAL WILL BE VINYL COATED UPHOLSTERY FABRIC(ARTIFICIAL LEATHER) AS PER RDSO SPEC NO. RDSO/2008/CG-07 REV.1 OR LATEST.
- ALL STRUCTURAL PART CONSISTING OF CARBON STEEL.
- PAINING ACCORDING TO COLOUR RAL9005 MATT BLACK.
- GENERAL TOLERANCE OF FOAM ±10mm.
- HORIZONTAL SLIDING MOVEMENT FROM MIDDLE POSITION: 90 mm FORWARD AND 90 mm BACKWARD.
- ALL FASTENERS TORQUE TIGHTENED AS PER IS: 1367-8-2002.
- THIS SEAT IS OCCUPIED WITH AN INBUILT 360° ROTATION WITH AUTO LOCKING ARRANGEMENT.
- A ROBUST MECHANICAL DIAL SYSTEM FOR ADJUSTING THE RECLING ANGLE OF BACK OF CHAIR, OPERABLE FROM BOTH THE LEFT AND RIGHT SIDES WHILE SITTING ON CHAIR.
- SEAT TO BE SUPPLIED IN TWO PARTS (SEAT BACK +CUSHION WITH MECHANISM SEPARATELY) WHICH CAN EASILY BE DISMANTLED BY REMOVING BOLTS ON BOTH SIDES UNDER RECLINER.

****THIS DRAWING IS PROVISIONALLY APPROVED**

3	DY.CEE/D-III	DIMN 140, 585, 65, 200, 330±10 DELETED. DIMN 103, 4, 380±5 ARE ADDED. HEIGHT ADJUSTER & WEIGHT ADJUSTMENT CHANGED.	
2	DY.CEE/D-III	BASE PLATE & HOLE POSITION MODIFIED AS PER WAG-9HC DRIVER SEAT AND PEDESTAL DRAWING.	
1	DY.CEE/D-III	a) NOTE 7,9&10 CHANGED. NOTE 11& 12 DELETED. b) DRAWING MODIFIED AND SOME DIMENSIONS CHANGED.	
ALT. NO.	ALT. AUTHY.	DESCRIPTION	DATE

		CHITTARANJAN LOCOMOTIVE WORKS	
DRAWN BY (SSE/DRG.)			
CHECKED BY (AEE/D/CONV-I)			
**APPROVED BY DY.CEE/D-III			
SIZE	DRG NO.	ALT.NO.	
A1	1211-01.131-001	3	
NTS			SHEET 1 OF 1